



### Product Information

Product Type	Aluminium Foil Pre-Cut Lid
Shape	95mm Pre-Cut Lid
Heat Seal Layer	Omniseal
Thickness	37
Weight (g/m2)	109.7 g/m2
Tolerance (+/-)	+/- 9.0 g/m2
Colour	Silver
Food Approval	Yes
Closure Type	Heat Seal
Protective Collar	No
Artwork Available?	Yes 4 colours max



### Technical Specification

Materials	Easy Peel, Sealing to PET, PS, PVC, PP, PE—Excellent product resistance: Barrier Properties, Light –total, Water Vapour—Total, Oxygen - Total, Aroma—Total
Approval	All raw materials and masterbatches used in the production process have the appropriate food contact.
Colours	White is also available for this product, MOQ applies.
Sealing Characteristics	Sealing temperature 180-220° C, Sealing Cycle Time 1.0 Second, Sealing Pressure 5.5 Bar Pressure. Optimum seal depends on sealing pressure time, temperature, container type as well as condition and performance of sealing heads.
Storage	12 Months from date of manufacture. Order record and product samples retained for 13 months.
Sustainability	Recycled Content: 0% Post Consumer Recycled Content 0% Recyclability: Check with local authority

### Palletisation

Item	Pieces per Box	Pieces per Pallet	Boxes per Pallet	Box Size (CM)	Total Pallet Height (CM)
3031	1000	50,000	50	10x10x10	500